

CATALOGUE



CHAIN SAWS, BRUSH CUTTERS, TRIMMERS

MAKE / MODEL	CYLINDER	PISTON ASSEMBLY		DETAILS		SIZE	REFERENCE NO.
	DIAMETER	PISTON	GUDGEON PIN	RINGS		M.M./INCH GROUP	PISTON ASSY/PISTON/PISTON RINGS
		CH + DH TH. (MM.) CROWN SHAPE	DIAMETER X LENGTH (M.M.)	COMBINATION & TYPE PER SET	AXIAL HEIGHT		

ABBREVIATION :-

1P - 1 Plain Compression Ring

2P - 2 Plain Compression Ring

x - Lock Pin Relief made on Upper side (Upper Side Notch)

Y - Lock Pin Relief made on Lower side (Lower side Notch)

z - Lock Pin Relief made on Internal side (Internal Notch)

Ph - Phosphating

1Px -1 Plain Upper side notch Compression Ring

2Px - 2 Plain Upper side notch Compression Ring

1PxPh - 1 Plain Upper side notch Compression Phosphating Ring

2PxPh - 2 Plain Upper side notch Compression Phosphating Ring

1Py -1 Plain Lower side notch Compression Ring

2Py -2 Plain Lower side notch Compression Ring

1PyPh -1 Plain Lower side notch Compression Phosphating Ring

2PyPh -2 Plain Lower side notch Compression Phosphating Ring

1Pz - 1 Plain Internal notch Compression Ring

2Pz - 2 Plain Internal notch Compression Ring

1PzPh - 1 Plain Internal notch Compression Phosphating Ring

2PzPh - 2 Plain Internal notch Compression Phosphating Ring

C - Running Face Chromium

CH- Compression Height

DH- Dome Height

TH- Total Height

Numeric No - Piston Crown shape

(1,2,3-----etc)