

CATALOGUE



CHAIN SAWS, BRUSH CUTTERS, TRIMMERS

MAKE / MODEL	CYLINDER	PISTON ASSEMBLY		DETAILS		SIZE	REFERENCE NO.
	DIAMETER	PISTON	GUDGEON PIN	RINGS		M.M./INCH GROUP	PISTON ASSY/PISTON/PISTON RINGS
		CH + DH TH. (MM.) CROWN SHAPE	DIAMETER X LENGTH (M.M.)	COMBINATION & TYPE PER SET	AXIAL HEIGHT		
SOLO							
SOLO PLV	48	25 + 3.6 47.2 2	12 x 40	2 PxPh	2	STD	ARSO-229/ SO-229/ SO-2290
SOLO PLV	48.5	25 + 3.6 47.2 2	12 x 40	2 PxPh	2	STD	ARSO-229A/ SO-229A/ SO-2290A

ABBREVIATION :-

- 1P - 1 Plain Compression Ring
- 2P - 2 Plain Compression Ring
- x - Lock Pin Relief made on Upper side (Upper Side Notch)
- Y - Lock Pin Relief made on Lower side (Lower side Notch)
- z - Lock Pin Relief made on Internal side (Internal Notch)
- Ph - Phosphating
- 1Px -1 Plain Upper side notch Compression Ring
- 2Px - 2 Plain Upper side notch Compression Ring
- 1PxPh - 1 Plain Upper side notch Compression Phosphating Ring
- 2PxPh - 2 Plain Upper side notch Compression Phosphating Ring
- 1Py -1 Plain Lower side notch Compression Ring
- 2Py -2 Plain Lower side notch Compression Ring
- 1PyPh -1 Plain Lower side notch Compression Phosphating Ring
- 2PyPh -2 Plain Lower side notch Compression Phosphating Ring
- 1Pz - 1 Plain Internal notch Compression Ring
- 2Pz - 2 Plain Internal notch Compression Ring
- 1PzPh - 1 Plain Internal notch Compression Phosphating Ring
- 2PzPh - 2 Plain Internal notch Compression Phosphating Ring
- C - Running Face Chromium
- CH- Compression Height
- DH- Dome Height
- TH- Total Height
- Numeric No - Piston Crown shape (1,2,3-----etc)